

## 1.3Mp HD Vandal IP Dome Camera - 20Mtr.



### Main Features

- ⇒ 1/3" 1.3 Megapixel progressive scan SONY CCD
- ⇒ H.264 & MJPEG dual-stream encoding
- ⇒ Max 12/15fps@1.3M(1280×720)&25/30fps@720P(1280x720)
- ⇒ Day/Night(ICR), 2DNR, Auto iris, AWB, AGC, BLC
- ⇒ 2.8~12mm varifocal lens
- ⇒ Built-in 2/1 alarm in/out
- ⇒ Micro SD memory, IP66, IK10, PoE
- ⇒ Mobile Software: CMOB
- ⇒ CMS Software: IPSS

Feature	Specification
Image Sensor	1/3" 1.3Megapixel PS CCD
Minimum Illumination	0.2lux/F1.4(color),0.01Lux/F1.4(B/W)
Shutter Speed	Auto/Manual,1/50~1/10000s
White Balance	Auto
Gain Control(AGC)	Auto/Manual
Lens	2.8~12mm
Video Compression	H.264/MJPEG
S/N Ratio	more than 50 dB
Back Light Compensation	BLC / HLC / DWDR
Video Streaming	Main Stream: 1.3M(1~12fps)/720P(1 ~ 25fps), Sub Stream: D1/CIF(1 ~ 25/30fps)
Video Output	1 channel BNC(1.0Vp-p, 75Ω)
Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576/704×480)/ CIF(352×288)
Snapshot	Fastest 1fps JPEG capture
Privacy Mask	Up to 4 areas
ICR	Auto(ICR) / Color / B/W
Audio Input	1 Channel
Audio Compression	G.711a / G.711u(64kbps) / PCM(128kbps)
Audio Output	1 Channel
Alarm IN	2 Channel
Alarm Out	1 Channel
Interface	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP,SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Ver. 2.0
User Account	10 users
Smart Phone	iPhone, iPad, Android, Windows Phone

Feature	Specification
Micro SD	SD, Max 32GB
Operating Temperature	-10°C~+60°C, 10%~90%
Power Source	DC12V/AC24V, PoE(802.3af)
Power Consumption	<8W
Weatherproof Standard	IK10 & IP66
Regulatory	CE, FCC and RoHS
Dimension	Φ160mm×118.5mm
Weight	1.25kg